

TECHNICAL SPECIFICATIONS VER. 1.		
PROJECT:	Түре:	
Voltage:	COMMENTS:	
	CORVEIGHT® 2008 NEVY	US LIGHTING INC

Step Light

SPECIFICATIONS FEATURES


Construction


Fixture housing is made of machined brass or aluminum and finished for lasting beauty and durability. Finishes include natural brass and aluminum, black aluminum and white aluminum. Spring mounting secures fixtures tightly into walls, ceilings or display cases. Compression fitting hold fibers tightly into fixture. 1.375" (35mm) diameter.

Cabling

The SL-500 accommodates 4 strand through 75 strand EndGlow cables (see Endglow Cable spec sheet for detailed cable information)








to be the focus of attention. A variety of finish

colors are available to suit any architectural,

commercial or retail decor. The SL500 series is

designed to work with EndGlow cabling.

SL502



ORDERING INFORMATION

MODEL	ENDGLOW CABLES
SL500 - BRASS	(Order Separately)
SL501 - ALUMINUM	SV4EG - 4 FIBERS
SL502 - ALUMINUM-BLACK	SV8EG - 8 FIBERS
SL503 - ALUMINUM-WHITE	SV12EG - 12 FIBERS
	SV25EG - 25 FIBERS
	SV50EG - 50 FIBERS
	SV75EG - 75 FIBERS

Ordering Example: \$L500